

## Smile

### TECHNICAL DATA / 数据

#### MOUNTING / 安装

Mounting location / 安装位置:

Track Mounted/轨道安装

Type / 类型:

Track Mounted / 轨道式

#### ELECTRICAL / 电器参数

Voltage / 电压:

220-240V

Frequency / 频率:

50/60Hz

Dimming / 调光:

Depending on driver/取决于驱动

#### DIMENSION / 相关尺寸

Dimension / 尺寸:

Ø72\*126 mm

Height / 高度:

157mm

Cut out / 开孔:

NO

#### LIGHT / 灯具

Adjustability / 可调角:

355° Rotation/355°旋转

Light distribution / 照明方式:

Non-DIM

Track/轨道:

1Circuits//3 Circuits

#### LAMP DESCRIPTION / 光源参数

Lamp type / 光源类型:

COB

Colour rendering index (CRI) / 显色指数:

Ra>90

MacAdam / 色容差:

<3

#### NOMINAL FLUX / 光通量

2700K:8W 880lm

2700K:10W 1110lm

3000K:8W 920lm

3000K:10W 1150lm

3500K:8W 944lm

3500K:10W 1180lm

4000K:8W 976lm

4000K:10W 1220lm

#### OTHERS / 其他

LED life Time / 光源寿命:

> 50,000h - L80 - B10 (Ta 25°C)

Environment temperature / 温度环境:

-20°C-40°C

Ingress protection / 防护等级:

IP20

### PRODUCT DESCRIPTION / 产品描述

Track-mounted spotlight, large angle light, suitable for a variety of scenes, high color rendering COB chip, adding a pleasant filter to life.

轨道式安装射灯，大角度发光，适用于多种场景，高显色COB芯片，为生活增添令人愉悦的滤镜。

### PROJECT / 项目

### TYPE / 类型

### NOTES / 笔记


### QUANTITY / 数量

### DATE / 日期

### PHOTO / 图片



### DIMENSIONS / 尺寸



### PACKAGE CONTENT / 包装

QTN/CTN / 数量/箱:

--PCS/CTN

NW / 净重:

--KG/CTN

GW / 毛重:

--KG/CTN

Inner box size / 内盒尺寸:

- CM

Outer box size / 外箱尺寸:

- CM




### ORDER TEMPLATE / 订单模板

Type 类别	Series 系列	Power 功率	Code 识别码	CCT 色温	CRI 显指	Beam angle 光束角	Body Color 颜色	Dimming 调光	Code 识别码	Reflecoor 防眩杯颜色	Remark 备注
02 轨道式	02.188B01000	08 8W 10 10W	*	27 2700	G 90	35°55 35°55°	SW 砂白 SB 砂黑	0 Non-DIM	*	A 砂白	-xx
				30 3000	H 97			1 TRIAC		D 砂黑	
				35 3500							
				40 4000							

Example/例如: 02.188B01000-08\*27G35°55SW0\*A(-XX)

LIGHT DISTRIBUTION / 配光曲线

3000K/8W




Luminous flux luminaire  
517lm (EXTREME CUT OFF)

Beam Angle:35°x55°

	h(m)	E(lx)	D(m)
1	253	0.58	
2	63	116	
3	28	174	
4	16	232	
5	10	290	

3000K/10W




Luminous flux luminaire  
638lm (EXTREME CUT OFF)

Beam Angle:35°x55°

	h(m)	E(lx)	D(m)
1	312	0.58	
2	78	116	
3	34	174	
4	19	232	
5	12	290	

APPLY TO / 适用于



1 CIRCUITS TRACK SURFACE  
两线轨道



220V

220V~250V 16A Max.



SIZE(mm)

1000

2000

3000

PRODUCT NAME

Track / 轨道

Track / 轨道


Track / 轨道

ORDER CODE

TL-0210

TL-0220


TL-0230



109x35x19

Power feeder unit/电源输入端


TL-0235



78x34x19

Linear(connector)/电源接驳器


TL-0231



70x70x17

L-connector/L型电源接驳器


TL-0232



105x70x17

T-connector/T型电源接驳器


TL-0233



105x105x17

X-connector/X型电源接驳器


TL-0234



280x35x19

Linear flexible/电源接驳器

TL-0236




31x34x19

End caps/堵头 (套)

TL-0237

APPLY TO / 适用于



1 CIRCUITS TRACK SURFACE  
三线轨道



220V

单相电 230V 16A Max. & 120V 20A Max.



SIZE(mm)

1000

PRODUCT NAME

Track / 轨道

ORDER CODE

TL-0310

2000


Track / 轨道

TL-0320

3000

Track / 轨道


TL-0330



108.5x35x18

Power feeder unit/电源输入端


TL-0335



80x35x18

Linear(connector)/电源接驳器


TL-0331



182x35x18

Linear(connector)/电源接驳器


TL-0331L



108.5x108.5x18

L-connector/L型电源接驳器


TL-0332



182x108.5x18

T-connector/T型电源接驳器


TL-0333



182x182x18

X-connector/X型电源接驳器

TL-0334



260x35x18

Linear flexible/电源接驳器

TL-0336




16.5x35x18

End caps/堵头 (套)

TL-0337

APPLY TO / 适用于




3 CIRCUITS/1 CIRCUITS DALI  
TRACK SURFACE  
四线三回路/四线DALI轨道




220V


单相电 230V 16A Max.



三相电 230V 3\*16A Max.



单相电 230V 16A Max.+DALI信号接线



SIZE(mm)

1000

2000

3000

PRODUCT NAME

Track / 轨道

Track / 轨道


Track / 轨道

ORDER CODE

PRO-0410

PRO-0420


PRO-0430



98x35x35

Power feeder unit/电源信号输入端


PRO-0431L/R



166x35x35

Linear(connector)/电源信号接驳器


PRO-0434



100x100x35

L-connector/L型电源信号接驳器


PRO-0435L/R



166x100x35

T-connector/T型电源信号接驳器


PRO-0436L1/R1/L2/R2



166x166x35

X-connector/X型电源信号接驳器


PRO-0437



68x21x35

Conductive connector/导电接驳器


PRO-0433



68x31x35

Insulated connector/绝缘接驳器


PRO-0433A



248x35x35

Linear flexible/电源信号接驳器

PRO-0439




35x35.5x31

End caps/堵头

PRO-0432


APPLY TO / 适用于




## 3 CIRCUITS DALI TRACK SURFACE 六线三回路轨道



单相电 230V 16A Max.



三相电 230V 3\*16A Max.



SIZE(mm)


1000  
2000  
3000

PRODUCT NAME

Track / 轨道  
Track / 轨道  
Track / 轨道

ORDER CODE

PRO-0610  
PRO-0620  
PRO-0630



139x35x35

Power feeder unit/电源信号输入端


PRO-0631L/R



107x21x35

Linear(connector)/电源信号接驳器


PRO-0633



203x35x35

Linear(connector)/电源信号接驳器


PRO-0634



119x119x35

L-connector/L型电源信号接驳器


PRO-0635L/R



203x119x35

T-connector/T型电源信号接驳器


PRO-0636L1/R1/L2/R2



203x203x35

X-connector/X型电源信号接驳器


PRO-0637



285x35x35

Linear flexible/电源信号接驳器

PRO-0639



264x35x35

Linear flexible/电源信号接驳器

PRO-0635



35x35.5x31

End caps/堵头

PRO-0432