

Cube

TECHNICAL DATA / 数据

MOUNTING / 安装

Mounting location / 安装位置: Ceiling / 天花安装
Type / 类型: Ceiling / 吸顶式

ELECTRICAL / 电器参数

Voltage / 电压: AC220-240V
Frequency / 频率: 50/60Hz
Dimming / 调光: Depending on driver / 取决于驱动

DIMENSION / 相关尺寸

Dimension / 尺寸: 42*42 mm
Height / 高度: 52 mm
Cut out / 开孔: NO
Min. recessed depth / 最小天花高度: NO

LIGHT / 灯具

Adjustability / 可调角: NO
Light distribution / 照明方式: Direct / 直接
Unified glare rating (UGR) / 防眩指数: --

LAMP DESCRIPTION / 光源参数

Lamp type / 光源类型: DOB
Colour rendering index (CRI) / 显色指数: Ra>90
MacAdam / 色容差: <3

NOMINAL FLUX / 光通量

2700K:5W 440lm
3000K:5W 450lm
4000K:5W 475lm


OTHERS / 其他

LED life Time / 光源寿命: > 50,000h - L80 - B10 (Ta 25°C)
Environment temperature / 温度环境: -20°C-40°C
Ingress protection / 防护等级: IP20

PHOTO / 图片



DIMENSIONS / 尺寸



PRODUCT DESCRIPTION / 产品描述

1. The stable DOB solution can be directly connected to the AC power for use, which realizes the extremely simple structure of the lamp, the diversified selection of optical effects, and the scope of practical scenarios is improved. 2. Different shapes can be made according to the collocation. It is small and exquisite, and can be controlled with one hand, which can realize the creation of space and show the value of space. 3. High color rendering and high luminous efficiency, natural light connection and transition, make the space bright and comfortable, the color rendering index is 90ra, anti-glare and no stroboscopic.

1、稳定DOB方案，可直接接通交流电进行使用实现了灯具结构的极度简洁，光学效果的多样化选择，实用场景范围得到提升。2、根据搭配做不同的造型，小巧精致，一手掌控，能实现空间创造，展现空间价值。3、高显色高光效，光线衔接过渡自然，能让空间敞亮舒适，显色指数90ra，防眩无频闪。

PACKAGE CONTENT / 包装

QTN/CTN / 数量/箱: 50PCS/CTN
NW / 净重: 4.6KG/CTN
GW / 毛重: 6.6KG/CTN
Inner box size / 内盒尺寸: 11×7.5×5CM
Outer box size / 外箱尺寸: 40×23×29 CM




ORDER TEMPLATE / 订单模板

Type 类别	Series 系列	Power 功率	Code 识别码	CCT 色温	CRI 显指	Beam angle 光束角	Body Color 颜色	Dimming 调光	Code 识别码	Reflector Color 防眩杯颜色	Remark 备注
03 吸顶式	204B01000	05 05W	*	27 2700	G 90	38 38°	SW 砂白	0 TRIAC	*	W 砂白	-xx
				30 3000	H 97	48 48°	SB 砂黑			B 砂黑	
				35 3500							
				40 4000							

Example/例如: 03.204B01000-05*27G38SW0*W(-XX)

LIGHT DISTRIBUTION / 配光曲线


3000K/5W



Luminous flux luminaire
223lm (EXTREME CUT OFF)

Beam Angle:38°

	h(m)	E(lx)	D(m)
1	356	07	
2	89	140	
3	40	210	
4	22	281	
5	14	351	



Luminous flux luminaire
235lm (EXTREME CUT OFF)

Beam Angle:48°

	h(m)	E(lx)	D(m)
1	295	09	
2	74	181	
3	33	271	
4	18	362	
5	12	452	