

NEOX

TECHNICAL DATA / 数据

MOUNTING / 安装

Mounting location / 安装位置:

Ceiling / 天花安装

Type / 类型:

Recessed / 嵌入式

ELECTRICAL / 电器参数

Voltage / 电压:

220-240V

Frequency / 频率:

50/60Hz

Dimming / 调光:

Depending on driver / 取决于驱动

DIMENSION / 相关尺寸

Dimension / 尺寸:

Ø108 mm

Height / 高度:

45 mm

Cut out / 开孔:

Ø90 mm

Min. recessed depth / 最小天花高度:

64 mm

LIGHT / 灯具

Adjustability / 可调角:

NO

Light distribution / 照明方式:

Direct / 直接

Unified glare rating (UGR) / 防眩指数:

<28

LAMP DESCRIPTION / 光源参数

Lamp type / 光源类型:

SMD

Colour rendering index (CRI) / 显色指数:

Ra>80/Ra>90

MacAdam / 色容差:

<3

NOMINAL FLUX / 光通量

2700K:7W980lm/10W1400lm

3000K:7W980lm/10W1400lm

4000K:7W980lm/10W1400lm

6000K:7W980lm/10W1400lm

OTHERS / 其他

LED life Time / 光源寿命:

> 50,000h - L80 - B10 (Ta 25°C)

Environment temperature / 温度环境:

-20°C-40°C

Ingress protection / 防护等级:

IP20

PRODUCT DESCRIPTION / 产品描述

Create a soft light effect, protect the eyes more intimately, and bring more possibilities to the space

打造柔和光效，护眼更贴心，给空间带来更多的可能。

PROJECT / 项目

TYPE / 类型

NOTES / 笔记


QUANTITY / 数量

DATE / 日期

PHOTO / 图片



DIMENSIONS / 尺寸



PACKAGE CONTENT / 包装

QTN/CTN / 数量/箱:

50PCS/CTN

NW / 净重:

8.7KG/CTN

GW / 毛重:

11KG/CTN

Inner box size / 内盒尺寸:

17.5×12×7.5 CM

Outer box size / 外箱尺寸:

62×38×41 CM




ORDER TEMPLATE / 订单模板

Type 类别	Series 系列	Power 功率	Code 识别码	CCT 色温	CRI 显指	Beam Angle 光束角	Body Color 颜色	Dimming 调光	Code 识别码	Reflector Color 防眩杯颜色	Remark 备注
01 嵌入式	170B02000	7 7W 10 10W	*	27 2700	E 80	100 100°	SW 砂白 SB 砂黑	0 Non-DIM	*	W 砂白 B 砂黑	-xx
				30 3000	G 90			1 TRIAC			
				40 4000				2 0/1-10V			
				60 6000				3 DALI			
				30 3000				5 BLE			
				60 6000				6 ZIGBEE			


Example/例如: 01170B02000-7*30E100SW0*W(-XX)

LIGHT DISTRIBUTION / 配光曲线

Ra=80 /3000K/7W



Ra=90 /3000K/10W



Ra=80 /3000K/10W

