

Mino

TECHNICAL DATA

MOUNTING

Mounting location: Ceiling
Type: Suspended

ELECTRICAL

Voltage: 220V
Frequency: 50/60Hz
Dimming: Depending on driver

DIMENSION

Dimension: Ø28 mm
Height: 600 mm
Cut out: NO
Min. recessed depth: NO

LIGHT

Adjustability: NO
Light distribution: Direct
Unified glare rating(UGR): <10

LAMP DESCRIPTION

Lamp type: SMD
Colour rendering index (CRI): Ra>90
MacAdam: <3

NOMINAL FLUX

2700K:3W321lm
3000K:3W339lm
3500K:3W348lm
4000K:3W360lm

OTHERS

LED life Time: > 50,000h - L80 - B10 (Ta 25°C)
Environment temperature: -20°C-40°C
Ingress protection: IP20

PRODUCT DESCRIPTION

A simple pendant light, recessed and surface mounted for your choice, suitable for high-end residential, hotels, commercial stores and other applications.

PROJECT

TYPE

NOTES


QUANTITY

DATE

PHOTO



DIMENSIONS



PACKAGE CONTENT

QTN/CTN: 9PCS/CTN
NW: 6.3KG/CTN
GW: 8.3KG/CTN
Inner box size: 8.5×8.5×72 CM
Outer box size: 74×27×27 CM




DATA

Type	Model No.	Code No.	Power	CCT	CRI	Beam Angle	Body Color	Dimming	Reflector Color	Remark
Suspended	MN7203	04.007D60000	3W	2700K 3000K 3500K 4000K	90	Spot 16° Medium 24°	Sand black Sand white	Non-DIM	Sand black Sand white Gold	-xx

LIGHT DISTRIBUTION

3000K/3W




Luminous flux luminaire
195lm (EXTREME CUT OFF)

Beam Angle:16°

h(m) E(lx) D(m)

1	16611	0.29
2	415	0.58
3	185	0.87
4	104	1.16
5	66	1.45



Luminous flux luminaire
198lm (EXTREME CUT OFF)

Beam Angle:24°

h(m) E(lx) D(m)

1	942	0.43
2	236	0.86
3	105	1.29
4	59	1.72
5	38	2.16