

Mino

TECHNICAL DATA

MOUNTING

Mounting location: Ceiling
Type: Suspended

ELECTRICAL

Voltage: 220V
Frequency: 50/60Hz
Dimming: Depending on driver

DIMENSION

Dimension: Ø52 mm
Height: 330 mm
Cut out: Ø40 mm
Min. recessed depth: 36.5 mm

LIGHT

Adjustability: NO
Light distribution: Direct
Unified glare rating (UGR): <16

LAMP DESCRIPTION

Lamp type: COB
Colour rendering index (CRI): Ra>80
MacAdam: <5

NOMINAL FLUX

2700K:8W784lm / 10W980lm
3000K:8W840lm / 10W1050lm
3500K:8W856lm / 10W1070lm
4000K:8W880lm / 10W1100lm

OTHERS

LED life Time: > 50,000h - L80 - B10 (Ta 25°C)
Environment temperature: -20°C-40°C
Ingress protection: IP20

PRODUCT DESCRIPTION

A simple pendant lamp with embedded installation mode is suitable for high-end residential, hotel, commercial stores and other applications.

PROJECT

TYPE

NOTES


QUANTITY

DATE

PHOTO



DIMENSIONS



PACKAGE CONTENT

QTN/CTN: 20PCS/CTN
NW: 13KG/CTN
GW: 15KG/CTN
Outer box size: 39.2×10×7.5 CM
52×40.5×32 CM




DATA

Type	Model No.	Code No.	Power	CCT	CRI	Beam Angle	Body Color	Dimming	Reflector Color	Remark
Suspended	MN8008 MN8010	04.002A33000	8W	2700K	90	Spot 18°	Sand black	Non-DIM	Sand black	-xx
			10W	3000K		Medium 23°	Sand white	0/1-10V	Sand white	
				3500K		Medium 32°	Red	DALI	Red	
				4000K			Yellow		Yellow	

LIGHT DISTRIBUTION


3000K/8W



Beam Angle:18°

	h(m)	E(lx)	D(m)
1	25411	0.39	
2	635	0.78	
3	282	1.17	
4	159	1.56	
5	102	1.95	


Luminous flux luminaire
528lm (EXTREME CUT OFF)



Beam Angle:23°


	h(m)	E(lx)	D(m)
1	28761	0.44	
2	719	0.89	
3	320	1.33	
4	180	1.78	
5	115	2.22	

Luminous flux luminaire
626lm (EXTREME CUT OFF)



Luminous flux luminaire
675lm (EXTREME CUT OFF)


3000K/10W



Beam Angle:18°

	h(m)	E(lx)	D(m)
1	3101	0.39	
2	775	0.78	
3	345	1.17	
4	194	1.56	
5	124	1.95	


Luminous flux luminaire
642lm (EXTREME CUT OFF)



Beam Angle:23°

	h(m)	E(lx)	D(m)
1	3564	0.44	
2	891	0.89	
3	396	1.33	
4	223	1.78	
5	143	2.22	

Luminous flux luminaire
774lm (EXTREME CUT OFF)



Luminous flux luminaire
823lm (EXTREME CUT OFF)