KClighting

PROJECT

TYPE

NOTES

QUANTITY

DATE

Mino

TECHNICAL DATA

MOUNTING

Mounting location:	Ceiling
Type:	Suspended

ELECTRICAL

Voltage:	220V
Frequency:	50/60Hz
Dimming:	Depending on driver

DIMENSION

Dimension:	Ø28 mm
Height:	200 mm
Cut out:	Ø35 mm
Min. recessed depth:	36.5 mm

LIGHT

Adjustibility:	NO
Light distribution:	Direct
Unified glare rating(UGR):	<10

LAMP DESCRIPTION

Lamp type:	SMD
Colour rendering index (CRI):	Ra>90
MacAdam:	<3

NOMINAL FLUX

2700K:3W321lm
3000K:3W339lm
3500K:3W348lm
4000K:3W360lm


OTHERS

LED life Time:	> 50,000h - L80 - B10 (Ta 25°C)
Environment temperature:	-20°C~40°C
Ingress protection:	IP20

PHOTO



DIMENSIONS



PRODUCT DESCRIPTION

A simple pendant light,recessed and surface mounted for your choice, suitable for high-end residential, hotels, commercial stores and other applications.

PACKAGE CONTENT

QTN/CTN:	30PCS/CTN
NW:	7.5KG/CTN
GW:	9.5KG/CTN
Inner box size:	8.5×8.5×32 CM
Outer box size:	53×45×34 CM


DATA

Type	Model No.	Code No.	Power	CCT	CRI	Beam Angle	Body Color	Dimming	Reflector Color	Remark
Suspended	MN6003	04.007C20000	3W	2700K 3000K 3500K 4000K	90	Spot 16° Medium 24°	Sand black Sand white	Non-DIM	Sand black Sand white Gold	-xx

LIGHT DISTRIBUTION

3000K /3W






Luminous flux luminaire
1951m (EXTREME CUT OFF)

Beam Angle:16°

h(m)	E(lx)	D(m)
1	16611	0.29
2	415	0.58
3	185	0.87
4	104	1.16
5	66	1.45





Luminous flux luminaire
1981m (EXTREME CUT OFF)

Beam Angle:24°

h(m)	E(lx)	D(m)
1	942	0.43
2	236	0.86
3	105	1.29
4	59	1.72
5	38	2.16

Guangdong KC Lighting Co.,Ltd
Tel: +86 760 22389158/+86 760 22382108 Fax: +86 760 22382109
Email: info@kclighting.hk Web: www.kclighting.hk
No. 13 Lianbao Road, Xiaolan Town, Zhongshan City