

IT70

TECHNICAL DATA / 数据

MOUNTING / 安装

Mounting location / 安装位置: Magnetic/磁吸安装
Type / 类型: Magnetic /磁吸

ELECTRICAL / 电器参数

Voltage / 电压: 48V
Frequency / 频率: --
Dimming / 调光: Depending on driver /取决于驱动

DIMENSION / 相关尺寸

Dimension / 尺寸: Ø70*130 mm
Height / 高度: 197 mm
Cut out / 开孔: NO
Min.recessed depth / 最小天花高度: NO

LIGHT / 灯具

Adjustability / 可调角: 365° Rotation|90° Tilting/365°旋转|90° 倾斜
Light distribution / 照明方式: Direct/直接
Unified glare rating(UGR) / 防眩指数: <22

LAMP DESCRIPTION / 光源参数

Lamp type / 光源类型: COB
Colour rendering index (CRI) / 显色指数: Ra>90
MacAdam / 色容差: <3

NOMINAL FLUX / 光通量

2700K:25W 3200lm
3000K:25W 3350lm
3500K:25W 3475lm
4000K:25W 3550lm

OTHERS / 其他

LED life Time / 光源寿命: > 50,000h - L80 - B10 (Ta 25°C)
Environment temperature / 温度环境: -20°C-40°C
Ingress protection / 防护等级: IP20

PRODUCT DESCRIPTION / 产品描述

Magnetic lighting system as a new generation of lighting solutions, through the track layout consistent with the decoration style, lamps in the form of modules, convenient disassembly, flexible movement and other features of free combination. It not only attention to both the key lighting and basic lighting functions. Thoroughly change before need to cut hole, wiring and other troublesome installation way, totally accord with the trend of current minimalism style popularity.

磁吸照明系统作为新一代照明解决方案, 通过与装修风格一致的轨道布局, 灯具以模块形式, 便捷的拆装、灵活移动等特点自由组合, 既可以兼顾重点照明和基础照明功能。彻底改变以往需要开孔、布线等烦恼的安装方式, 非常符合当下极简风格流行的趋势。

ORDER TEMPLATE / 订单模板

Type 类别	Series 系列	Power 功率	Code 识别码	CCT 色温	CRI 显指	Beam angle 光束角	Body Color 颜色	Dimming 调光	Code 识别码	Reflector Color 防眩杯颜色	Remark 备注
07 磁吸	006A01000	25 25W	*	27 2700	G 90	15 15°	SW 砂白	0 Non-DIM	*	W 砂白	-xx
				30 3000	H 97	25 25°	SB 砂黑	2 0/1-10V		B 砂黑	
				35 3500		36 36°	RR 青古铜	3 DALI		G 金色	
				40 4000		50 50°	CP 镀铬	5 BLE		Q 青古铜	
				27 2700				6 ZIGBEE		C 铬色	
				60 6000							

Example/例如: 07.006A01000-25*27G15-36SW0*W(-XX)

PROJECT / 项目

TYPE / 类型

NOTES / 笔记



QUANTITY / 数量

DATE / 日期

PHOTO / 图片



DIMENSIONS / 尺寸




PACKAGE CONTENT / 包装

QTN/CTN / 数量/箱: 20PCS/CTN
NW / 净重: 11.5KG/CTN
GW / 毛重: 13.5KG/CTN
Inner box size / 内盒尺寸: 25.2×19.5×7.5 CM
Outer box size / 外箱尺寸: 52×40×40 CM



LIGHT DISTRIBUTION / 配光曲线


3000K/25W



Luminous flux luminaire
2022lm (EXTREME CUT OFF)

Beam Angle:15°


	h(m)	E(lx)	D(m)
1	19004	0.26	
2	4751	0.52	
3	2112	0.78	
4	1188	1.05	
5	760	1.31	



Luminous flux luminaire
2072lm (EXTREME CUT OFF)

Beam Angle:25°


	h(m)	E(lx)	D(m)
1	10764	0.45	
2	2691	0.90	
3	1196	1.34	
4	673	1.79	
5	431	2.24	



Luminous flux luminaire
1967lm (EXTREME CUT OFF)

Beam Angle:36°

	h(m)	E(lx)	D(m)
1	4875	0.65	
2	1219	1.30	
3	542	1.94	
4	305	2.59	
5	195	3.24	




Luminous flux luminaire
1937lm (EXTREME CUT OFF)

Beam Angle:60°

	h(m)	E(lx)	D(m)
1	2133	1.12	
2	533	2.24	
3	237	3.36	
4	133	4.48	
5	85	5.60	

APPLY TO / 适用于



MINI TRACK M26A suspended indirect 迷你磁吸轨道M26A 吊线式



48V



inset single control via KC BLE Mesh app

1	Non-DIM
2	0/1-10V
3	DALI
4	BLE
5	ZIGBEE



SIZE(mm)/尺寸

1000

2000

3000

PRODUCT NAME/产品名称

Track rail/磁吸轨道

Track rail/磁吸轨道

Track rail/磁吸轨道

ORDER CODE/型号

07.M26A10000

07.M26A20000

07.M26A30000



100x100

Channel corner*V90°/垂直转角

07.M26AV9000



100x100

Channel corner*H90°/水平转角

07.M26AH9000



100x100

Channel corner*E90°/垂直外转角

07.M26AE9000



77x77

+ Shped corner*90°/水平十字转角


07.M26A+9000



180x77x77

T Shped corner*90°/水平T字转角


07.M26AT9000



130x17x16 Apply to 500mm

Power feeder unit/电源信号输入端

07.M26L01000



130x17x16 Apply to 2000mm

Power feeder unit/电源信号输入端

07.M26L02000



130x17x16

Linear flexible/电源信号转接器


07.M26L03000



124x17x16/160x22

Linear/信号接驳器


07.M26L04000



54x26

End caps/堵头 (套)

07.M26L05000



20

Lock line/锁线器


2000

Suspension cable/吊线

07.M26L06000

35x22.5

Sonconnector/连接件



2000x65

Pendant Kit/吊线装备 (套)

07.M26L07000



405x22x42

Insert power supply/一体式电源

07.M26L10000



215x115x30

Power supply /VHP/200W/48V驱动

2.01.MW022




215x115x30

Power supply /LRS/350W/48V驱动

2.01.MW023

APPLY TO / 适用于



MINI TRACK M26T Trimless 迷你磁吸轨道M26T 预埋式




48V



inset single control via KC BLE Mesh app

1	Non-DIM
2	0/1-10V
3	DALI
4	BLE
5	ZIGBEE



SIZE(mm)/尺寸

1000

2000

3000

PRODUCT NAME/产品名称

Track rail/磁吸轨道

Track rail/磁吸轨道

Track rail/磁吸轨道

ORDER CODE/型号

07.M26T10000

07.M26T20000

07.M26T30000



100x100

Channel corner*V90°/垂直转角

07.M26TV9000



100x100

Channel corner*H90°/水平转角

07.M26TH9000



100x100

Channel corner*E90°/垂直外转角

07.M26TE9000



77x77

+ Shped corner*90°/水平十字转角


07.M26T+9000



180x77x77

T Shped corner*90°/水平T字转角

07.M26TT9000



130x17x16 Apply to 500mm

Power feeder unit/电源信号输入端


07.M26L01000



130x17x16 Apply to 2000mm

Power feeder unit/电源信号输入端

07.M26L02000



130x17x16

Linear flexible/电源信号转接器


07.M26L03000



124x17x16/160x22

Linear/信号接驳器


07.M26L04000



54x26

End caps/堵头 (套)

07.M26L05000



405x22x42

Insert power supply/一体式电源

07.M26L10000

215x115x30

Power supply /VHP/200W/48V驱动


2.01.MW022

215x115x30

Power supply /LRS/350W/48V驱动

2.01.MW023

APPLY TO / 适用于




MINI TRACK M26R Trim 迷你磁吸轨道M26R 嵌入式



inset single control via KC BLE Mesh app

1	Non-DIM
2	0/1-10V
3	DALI
4	BLE
5	ZIGBEE



SIZE(mm)/尺寸

1000
2000
3000

PRODUCT NAME/产品名称

Track rail/磁吸轨道
Track rail/磁吸轨道
Track rail/磁吸轨道

ORDER CODE/型号

07.M26R10000
07.M26R20000
07.M26R30000



100x100

Channel corner*V90°/垂直转角

07.M26RV9000



100x100

Channel corner*H90°/水平转角

07.M26RH9000



100x100

Channel corner*E90°/垂直外转角

07.M26RE9000



77x77

+ Shped corner*90°/水平十字转角


07.M26R+9000



180x77x77

T Shped corner*90°/水平T字转角

07.M26RT9000




130x17x16

Apply to 500mm

Power feeder unit/电源信号输入端

07.M26L01000




130x17x16

Apply to 2000mm

Power feeder unit/电源信号输入端

07.M26L02000



130x17x16

Lineair flexible/电源信号转接器


07.M26L03000



124x17x16/160x22

Linear/信号接驳器


07.M26L04000



54x26

End caps/堵头 (套)

07.M26L05000



405x22x42

Insert power supply/一体式电源

07.M26L10000

215x115x30

Power supply /VHP/200W/48V驱动


2.01.MW022

215x115x30

Power supply /LRS/350W/48V驱动

2.01.MW023

APPLY TO / 适用于



MINI TRACK M26E Trimless 迷你磁吸轨道M26E 预埋式




48V



tuya

inset single control via KC BLE Mesh app

1	Non-DIM
2	0/1-10V
3	DALI
4	BLE
5	ZIGBEE



SIZE(mm)/尺寸

1000

2000

3000

PRODUCT NAME/产品名称

Track rail/磁吸轨道

Track rail/磁吸轨道

Track rail/磁吸轨道

ORDER CODE/型号

07.M26E10000

07.M26E20000

07.M26E30000



100x100

Channel corner*V90°/垂直转角

07.M26EV9000



100x100

Channel corner*H90°/水平转角

07.M26EH9000



100x100

Channel corner*E90°/垂直外转角

07.M26EE9000



77x77

+ Shped corner*90°/水平十字转角


07.M26E+9000



180x77x77

T Shped corner*90°/水平T字转角


07.M26ET9000



130x17x16 Apply to 500mm

Power feeder unit/电源信号输入端


07.M26L01000



130x17x16 Apply to 2000mm

Power feeder unit/电源信号输入端

07.M26L02000



130x17x16

Linear flexible/电源信号转接器


07.M26L03000



124x17x16/160x22

Linear/信号接驳器


07.M26L04000



54x26

End caps/堵头 (套)

07.M26L05000



405x22x42

Insert power supply/一体式电源

07.M26L10000

215x115x30

Power supply /VHP/200W/48V驱动

2.01.MW022

215x115x30

Power supply /LRS/350W/48V驱动

2.01.MW023

GUANGDONG KC LIGHTING CO.,LTD

Tel:86 760 22389158 22382108 Fax:86 760 22382109

Email:info@kclighting.hk www.kclighting.hk

No.11 Tongfu South Road,Guzhen Town,Zhongshan City.

2022-8-18 / 18:00